

Ultimate flexibility, inside and out...

Searching for an easy-to-use durable tablet with a great list of unique features for ultimate flexibility and free of charge software to ease the management and integration of the devices? It's time to choose the high quality, rugged TB100.

Unique built-in 3,75G

Tablets are increasingly being used in business environments, like instore retail and mobile POS to support employees in answering customer requests, presenting new products and services and keeping a clear inventory overview.

Thanks to the integrated 3,75G feature, the TB100 is also a great solution for field service and sales automation. Employees working outside the four walls in need of a great mobile solution with secured data storage and transfer now find all required features and more in one device

Rugged tablet with Gorilla® glass

As a professional tablet user you need a tablet to be scratch and bump-resistant. During working hours accidents happen but buying tablets on a regular basis to replace the old ones doesn't fit into any commercial business strategy.

That's why the TB100 is equipped with a 7" WXGATFT LCD multitouch display of Gorilla® glass. This type of glass is not only offering

excellent visibility inside as well as outside, it's also a very durable which increases the product life time of the device. The combination of this unique glass with an anti-slipping rubber protection around the main body, an IP65 rating against moisture and dust and a 1.2m drop MIL standard, makes this tablet is THE solution for all your business demands. Don't settle with a consumer grade tablet, choose a long term solution!

Additional Pocket Size CCD scanner

To expand the large list of TB100's unique features, a pocket size CCD scanner is available for intensive scanning purposes: the Unitech MS910. Connect the MS910 to the tablet by Bluetooth and the TB100 becomes a mobile solution for any application that requires a scanning possibility. Because of the matching exterior colors the MS910 and TB100 together look like an all-in-one device.

Main Features:

- First built-in 3,75G rugged tablet weighing less than 600 grams
- Android™ v3.2 operating system
- Gorilla® glass, 7" WXGA multi-touch TFT LCD display
- High capacity battery with 6 hours battery life
- WLAN 802.11 b/g/n, Bluetooth® 2.1 EDR, 3,75G (optional)
- Optional pocket size CCD scanner available
- Remote device management: 12Manage
- IP65 and 1.2m drop MIL standard



TB100 Specifications

Operation System

Processor NVIDIA® Tegra™ 2 1.0 GHz

Dual Core Processor System Memory DDR2 1GB SDRAM

Flash ROM:512MB

OS Android™ v3.2 - API Level 13

Storage 16GB eMMC Flash
Other Built-in Light Sensor
Built-in G-Sensor

Built-in 3-axis digital gyroscope

Built-in Vibration motor

Display

Type touch screen Projected Capacitive

Multi-Touch Panel

Light Transmission ≥ 87%

Display Type 7" WXGA 16:10 TFT LCD

Max. Resolution 1280 x 800 Screen material Gorilla® glass

Max. Color 262K

Dot Size 0.117755(H) x 0.117755(V)

Luminance 400 cd/m2

View Angle Horizontal 178° (Typical)

Vertical 178° (Typical)

Camera / Photos / Video

Camera Front: 1.2M Pixel camera

Rear: 5M Pixel AF camera

Communication

WLAN 802.11 b/g/n PAN Bluetooth® 2.1 EDR

WWAN 3,75G modem module (optional)

Navigation GPS, Digital Compass

Audio

3.5mm stereo headphone jack Built- speaker & microphone

Power Source

AC/ DC Adapter AC Power input: 100V-240V,

50Hz-60Hz, 12V/2A, 24W DC Power output: 12V/ 2A

Battery Li-Polymer high capacity battery

(27Whr)

Operating time 6 hours

Expansion Slot

1x DC-IN Jack 1x Mini USB Port 1x Mini HDMI Port 1x Micro SD Card Slot

Enclosure

Weight <600g, TBC

Dimension 136.6mm x 218mm x 21mm, TBC

Color Black, TBC

Environmental

Operating temperature -20 to 60°C Storage temperature -55 to 75°C

Relative Humidity 10 to 95% @ 40°C,

non-condensing
Drop Specification 26 drops of 48 ir

26 drops of 48 inches/1.2m height to 2" plywood over concrete with

unit off Mil Std 810G-516.6,

Procedure IV IP65, Compliance

Air +/- 8KV, Contact +/- 4KV Meets Mil Std 810G-514.6,

Procedure I Cat. 24, Fig. 514.6E-1 & 514.6E-2 (Unit is non-operating) ASTM 4169-99 Truck Assurance

12Manage and 12Solutions are

Level II, Schedule E (Unit is operating)

Software

ESD

Vibration



Environmental Sealing

Unitech's software solutions to enhance device deployment and remote management. This software improves system reliability, reduces

running smootly.

More info: www.unitechnical.info

service costs and ensures systems

Accessories

Power cord Holster Vehicle holder Cigarette light charger

MS910 Pocket scanner

Regulatory Approvals

CE, FCC, Class B/UL

Unitech Europe

Tilburg, The Netherlands

• Tel: +31 (0)13 460 9292 • Email: Info@eu.ute.com

• Website: http://eu.ute.com



A \



Gorilla® glass is a trademark of Corning Incorporated

Unitech America Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan